



# Material Safety Data Sheet

Document Code: A100-Latex  
Version: 01a

Date of Preparation  
October 23, 2001

## Section 1 - Product and Company Identification

### PRODUCT NAME & NUMBERS

#### A-100® Exterior Latex Flat

Tricorn Black	A6B550	Perma White	(A6W501)
Base C	A6G514	Base A	A6W515
Chateau Brown	(A6N507)	Ultra Deep	A6W520
Plantation Brown	(A6N556)	Tinting White	(A6W596)
Burgundy	A6R533	Base B	A6Y516
White	(A6W16)	Yellow Corn	A6Y554
Extra White	A6W51		

### HMIS CODES

Health	2*
Flammability	0
Reactivity	0

#### A-100® Exterior Latex Satin

Tricorn Black	A82B550	Perma White	(A82W501)
Base C	A82G514	White	(A82W510)
Chateau Brown	(A82N507)	Base A	A82W515
Plantation Brown	(A82N556)	Tinting White	(A82W596)
Burgundy	A82R533	Base B	A82Y516
Extra White	A82W51	Yellow Corn	A82Y554

#### A-100® Exterior Latex Gloss

Tricorn Black	A8B512	Extra White	A8W51
Base C	A8G531	Perma White	(A8W524)
Plantation Brown	(A8N503)	Tinting White	(A8W525)
Chateau Brown	(A8N515)	Base A	A8W541
Burgundy	A8R533	Yellow Corn	A8Y520
White	(A8W16)	Base B	A8Y558

#### A-100® Exterior Latex Wood Primer

White	B42W41
-------	--------

MANUFACTURER'S NAME  
THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

EMERGENCY TELEPHONE NO.  
(216) 566-2917  
INFORMATION TELEPHONE NO.  
(216) 566-2902

## Section 2 – Composition/Information on Ingredients

CAS Number	Ingredient Name	CAS Number	Ingredient Name
------------	-----------------	------------	-----------------

Listed products may contain the following ingredients based upon color.  
To obtain individual product MSDS or environmental data, call (216) 566-2902.

### Flat Colors

14808-60-7	Quartz
14464-46-1	Cristobalite
13463-67-7	Titanium Dioxide
1314-13-2	Zinc Oxide
1333-86-4	Carbon Black
8007-18-9	Nickel Antimony Titanate
107-21-1	Ethylene Glycol
1332-58-7	Kaolin
14807-96-6	Talc

### Satin Colors

64742-54-7	Heavy Paraffinic Oil
14464-46-1	Cristobalite
1332-58-7	Kaolin
13463-67-7	Titanium Dioxide
1314-13-2	Zinc Oxide
1333-86-4	Carbon Black
8007-18-9	Nickel Antimony Titanate
107-21-1	Ethylene Glycol
14807-96-6	Talc

## Section 2 – Composition/Information on Ingredients (continued)

CAS Number	Ingredient Name	CAS Number	Ingredient Name
<b>Gloss Colors</b>		<b>Latex Wood Primer</b>	
64742-54-7	Heavy Paraffinic Oil	112-34-5	2-(2-Butoxyethoxy)-ethanol
112-34-5	2-(2-Butoxyethoxy)-ethanol	107-21-1	Ethylene Glycol
14464-46-1	Cristobalite	14808-60-7	Quartz
1332-58-7	Kaolin	14464-46-1	Cristobalite
13463-67-7	Titanium Dioxide	14807-96-6	Talc
1314-13-2	Zinc Oxide	13463-67-7	Titanium Dioxide
1333-86-4	Carbon Black	1333-86-4	Carbon Black
8007-18-9	Nickel Antimony Titanate		
107-21-1	Ethylene Glycol		
14807-96-6	Talc		

% WT.	CAS No.	Ingredient Name	
<b>max 1</b>	<b>64742-54-7</b>	<b>Heavy Paraffinic Oil.</b>	
		ACGIH TLV 5 mg/m3 as Mist	
		OSHA PEL 5 mg/m3 as Mist	
<b>max 2</b>	<b>112-34-5</b>	<b>2-(2-Butoxyethoxy)-ethanol</b>	
		ACGIH TLV Not Established	0.1 mm
		OSHA PEL Not Established	
<b>max 3</b>	<b>107-21-1</b>	<b>Ethylene Glycol.</b>	
		ACGIH TLV 50 ppm CEILING	0.1 mm
		OSHA PEL 50 ppm CEILING	
<b>max 24</b>	<b>14808-60-7</b>	<b>Quartz</b>	
		ACGIH TLV 0.05 mg/m3 as Respirable Dust	
		OSHA PEL 0.05 mg/m3 as Respirable Dust	
<b>max 2</b>	<b>14464-46-1</b>	<b>Cristobalite</b>	
		ACGIH TLV 0.05 mg/m3 as Respirable Dust	
		OSHA PEL 0.05 mg/m3 as Respirable Dust	
<b>max 6</b>	<b>1332-58-7</b>	<b>Kaolin</b>	
		ACGIH TLV 2 mg/m3 as Respirable Dust	
		OSHA PEL 10 mg/m3 Total Dust	
		OSHA PEL 5 mg/m3 Respirable Fraction	
<b>max 7</b>	<b>14807-96-6</b>	<b>Talc</b>	
		ACGIH TLV 2 mg/m3 as Respirable Dust	
		OSHA PEL 2 mg/m3 as Respirable Dust	
<b>max 18</b>	<b>13463-67-7</b>	<b>Titanium Dioxide.</b>	
		ACGIH TLV 10 mg/m3 as Dust	
		OSHA PEL 10 mg/m3 Total Dust	
		OSHA PEL 5 mg/m3 Respirable Fraction	
<b>max 3</b>	<b>1314-13-2</b>	<b>Zinc Oxide</b>	
		ACGIH TLV 10 mg/m3 as Dust	
		OSHA PEL 10 mg/m3 Total Dust	
		OSHA PEL 5 mg/m3 Respirable Fraction	
<b>max 2</b>	<b>1333-86-4</b>	<b>Carbon Black.</b>	
		ACGIH TLV 3.5 mg/m3	
		OSHA PEL 3.5 mg/m3	
<b>max 8</b>	<b>8007-18-9</b>	<b>Nickel Antimony Titanate</b>	
<i>(Yellow Corn only)</i>		ACGIH TLV 0.5 mg/m3	
		OSHA PEL 0.5 mg/m3	

## Section 3 – Hazards Identification

### ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

### EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

### CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

## Section 4 – First Aid Measures

- If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
- If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
- If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- If SWALLOWED: Do not induce vomiting. Get medical attention immediately.

## Section 5 – Fire Fighting Measures

FLASH POINT	LEL	UEL
None	N.A.	N.A.

### FLAMMABILITY CLASSIFICATION

Not Applicable

### EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

### UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

### SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## Section 6 – Accidental Release Measures

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

## Section 7 – Handling and Storage

### DOL STORAGE CATEGORY

Not Applicable

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

## Section 8 – Exposure Controls/Personal Protection

### PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

Removing or disturbing old paint from interior or exterior surfaces by sanding, scraping, abrading or other means may produce dust, debris or fumes that contain lead. Exposure to lead dust, debris or fumes may cause brain damage or other adverse health effects, especially in children and pregnant women. Structures built before 1978 should be tested by a licensed inspector prior to removing or disturbing old paint. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

### VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

### RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding, wirebrushing, abrading, burning or welding the dried film, wear a particulate respirator approved by NIOSH/MSHA for protection against non-volatile materials in Section 2.

### PROTECTIVE GLOVES & EYE PROTECTION

Wear gloves recommended by glove supplier for protection against materials in Section 2. Wear safety spectacles with unperforated sideshields.

## Section 9 – Physical and Chemical Properties

PRODUCT WEIGHT	8.8-10.9 lb/gal	EVAPORATION RATE	Slower than Ether
SPECIFIC GRAVITY	1.06-1.32	VAPOR DENSITY	Heavier than Air
BOILING POINT	212-477 °F	MELTING POINT	N.A.
VOLATILE VOLUME	63-68 %	SOLUBILITY IN WATER	N.A.
pH	9.0-9.5		

### VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)

0.7-1.3 lb/gal Less Federally Exempt Solvents

0.3-0.5 lb/gal Emitted VOC

## Section 10 – Stability and Reactivity

### STABILITY

Stable

### CONDITIONS TO AVOID

None known.

### INCOMPATIBILITY

None known.

### HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide, Oxides of Metals in Section 2

### HAZARDOUS POLYMERIZATION

Will not occur

## Section 11 – Toxicological Information

### CHRONIC HEALTH HAZARDS

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Yellow Corn colors contain Nickel Antimony Titanate. Limited evidence exists linking certain Nickel compounds to cancer in animals and possibly humans, however no direct evidence exists that Nickel Antimony Titanate is carcinogenic.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

Rats exposed to titanium dioxide dust at 250 mg./m<sup>3</sup> developed lung cancer, however, such exposure levels are not attainable in the workplace.

### TOXICOLOGY DATA

CAS No.	Ingredient Name			
64742-54-7	<b>Heavy Paraffinic Oil.</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
112-34-5	<b>2-(2-Butoxyethoxy)-ethanol</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		5660 mg/kg
107-21-1	<b>Ethylene Glycol.</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		4700 mg/kg
14808-60-7	<b>Quartz</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
14464-46-1	<b>Cristobalite</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
1332-58-7	<b>Kaolin</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
14807-96-6	<b>Talc</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
13463-67-7	<b>Titanium Dioxide.</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		>7500 mg/kg
1314-13-2	<b>Zinc Oxide</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
1333-86-4	<b>Carbon Black.</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		>15400 mg/kg
8007-18-9	<b>Nickel Antimony Titanate</b>			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established

## Section 12 – Ecological Information

### ECOTOXICOLOGICAL INFORMATION

No Data Available.

## Section 13 – Disposal Considerations

### WASTE DISPOSAL METHOD

Waste from A6Y554, A8Y520, A82Y554 and B42W41 may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for extractability to determine the applicable EPA hazardous waste numbers.

Waste from other products is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate all products in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

## Section 14 – Transport Information

DOT PROPER SHIPPING DESCRIPTION: Paint and Related Materials, NOIBN

IATA/IMDG SHIPPING DESCRIPTION: Paint and Related Materials, NOIBN

## Section 15 – Regulatory Information

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
107-21-1	Ethylene Glycol.	max 3	
	Glycol Ethers	max 2	
	Zinc Compound.	0-3	0-2.1
	Nickel Compound. ( <i>Yellow Corn only</i> )	7-8	0.3
	Antimony Compound. ( <i>Yellow Corn only</i> )	7-8	1.0

### CALIFORNIA PROPOSITION 65

WARNING: These products contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

## Section 16 – Other Information

CANADIAN DISTRIBUTOR: *Sherwin-Williams Canada  
180 Brunel Rd.  
Mississauga, ON L4Z 1T5*

NOTE: These products have been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.