



# Material Safety Data Sheet

Document Code: Harmony  
Version: 01a

Date of Preparation  
October 10, 2001

## Section 1 - Product and Company Identification

### PRODUCT NAME & NUMBERS

**HARMONY** Interior Latex Flat Finish  
Extra White B5W951  
Deep Base B5W953

**HARMONY** Interior Latex Eg-Shel Finish  
Extra White B9W951  
Deep Base B9W953

**HARMONY** Interior Latex Semi-Gloss Finish  
Extra White B10W951  
Deep Base B10W953

### HMIS CODES

Health 1  
Flammability 0  
Reactivity 0

**HARMONY** Interior Latex Primer  
White B11W900

### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

### EMERGENCY TELEPHONE NO.

(216) 566-2917

### INFORMATION TELEPHONE NO.

(216) 566-2902

## Section 2 - Composition/Information on Ingredients

% WT.	CAS No.	Ingredient Name	Vapor Pressure
0.1 (except B5W951)	13463-41-7	<b>Zinc Pyrithione</b> ACGIH TLV Not Established OSHA PEL Not Established	
0-10	1332-58-7	<b>Kaolin</b> ACGIH TLV 2 mg/m3 as Respirable Dust OSHA PEL 10 mg/m3 Total Dust OSHA PEL 5 mg/m3 Respirable Fraction	
3 (B5W951 only)	12001-26-2	<b>Mica</b> ACGIH TLV 3 mg/m3 as Respirable Dust OSHA PEL 3 mg/m3 as Respirable Dust	
0-16	471-34-1	<b>Calcium Carbonate.</b> ACGIH TLV 10 mg/m3 as Dust OSHA PEL 15 mg/m3 Total Dust OSHA PEL 5 mg/m3 Respirable Fraction	
4-16	13463-67-7	<b>Titanium Dioxide.</b> ACGIH TLV 10 mg/m3 as Dust OSHA PEL 10 mg/m3 Total Dust OSHA PEL 5 mg/m3 Respirable Fraction	
<3% due to tinting	107-21-1	<b>Ethylene Glycol.</b> ACGIH TLV 50 ppm CEILING OSHA PEL 50 ppm CEILING	0.1 mm
<3% due to tinting	14807-96-6	<b>Talc</b> ACGIH TLV 2 mg/m3 as Respirable Dust OSHA PEL 2 mg/m3 as Respirable Dust	
<1% due to tinting	1333-86-4	<b>Carbon Black.</b> ACGIH TLV 3.5 mg/m3 OSHA PEL 3.5 mg/m3	

## Section 3 – Hazards Identification

### ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

### EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

### CANCER INFORMATION

FOR COMPLETE DISCUSSION OF TOXICOLOGY DATA REFER TO SECTION 11.

## Section 4 – First Aid Measures

- If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
- If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
- If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- If SWALLOWED: Do not induce vomiting. Get medical attention immediately.

## Section 5 – Fire Fighting Measures

FLASH POINT	LEL	UEL
None	N.A.	N.A.

### FLAMMABILITY CLASSIFICATION

Not Applicable

### EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

### UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

### SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## Section 6 – Accidental Release Measures

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

## Section 7 – Handling and Storage

### DOL STORAGE CATEGORY

Not Applicable

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

## Section 8 – Exposure Controls/Personal Protection

### PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

Removing or disturbing old paint from interior or exterior surfaces by sanding, scraping, abrading or other means may produce dust, debris or fumes that contain lead. Exposure to lead dust, debris or fumes may cause brain damage or other adverse health effects, especially in children and pregnant women. Structures built before 1978 should be tested by a licensed inspector prior to removing or disturbing old paint. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

### VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

### RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

### PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

### EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

## Section 9 – Physical and Chemical Properties

PRODUCT WEIGHT	9.2-12.1 lb/gal	EVAPORATION RATE	Slower than Ether
SPECIFIC GRAVITY	1.10-1.46	VAPOR DENSITY	Heavier than Air
BOILING POINT	212-213 °F	MELTING POINT	N.A.
VOLATILE VOLUME	58-67 %	SOLUBILITY IN WATER	N.A.
pH	9.0-9.5		
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)			
0.0 lb/gal	Less Federally Exempt Solvents		
0.0 lb/gal	Emitted VOC		

## Section 10 – Stability and Reactivity

### STABILITY

Stable

### CONDITIONS TO AVOID

None known.

### INCOMPATIBILITY

None known.

### HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

### HAZARDOUS POLYMERIZATION

Will not occur

## Section 11 – Toxicological Information

### CHRONIC HEALTH HAZARDS

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to Ethylene Glycol, which may be added during tinting, may cause adverse effects to the liver and urinary systems.

Rats exposed to titanium dioxide dust at 250 mg./m<sup>3</sup> developed lung cancer, however, such exposure levels are not attainable in the workplace.

### TOXICOLOGY DATA

CAS No.	Ingredient Name				
13463-41-7	<b>Zinc Pyrithione</b>	LC50	RAT	4HR	Not Established
		LD50	RAT		Not Established
1332-58-7	<b>Kaolin</b>	LC50	RAT	4HR	Not Established
		LD50	RAT		Not Established
12001-26-2	<b>Mica</b>	LC50	RAT	4HR	Not Established
		LD50	RAT		Not Established
471-34-1	<b>Calcium Carbonate.</b>	LC50	RAT	4HR	Not Established
		LD50	RAT		Not Established
13463-67-7	<b>Titanium Dioxide.</b>	LC50	RAT	4HR	Not Established
		LD50	RAT		>7500 mg/kg
107-21-1	<b>Ethylene Glycol.</b>	LC50	RAT	4HR	Not Established
		LD50	RAT		4700 mg/kg
14807-96-6	<b>Talc</b>	LC50	RAT	4HR	Not Established
		LD50	RAT		Not Established
1333-86-4	<b>Carbon Black</b>	LC50	RAT	4HR	Not Established
		LD50	RAT		>15400 mg/kg

## Section 12 – Ecological Information

### ECOTOXICOLOGICAL INFORMATION

No Data Available.

## Section 13 – Disposal Considerations

### WASTE DISPOSAL METHOD

Waste from these products is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

## Section 14 – Transport Information

DOT PROPER SHIPPING DESCRIPTION: Paint and Related Materials, NOIBN

IATA/IMDG SHIPPING DESCRIPTION: Paint and Related Materials, NOIBN

## Section 15 – Regulatory Information

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
107-21-1	Ethylene Glycol.	<3	

CALIFORNIA PROPOSITION 65

WARNING: These products, except for B11W900, contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. B11W900 contains chemicals known to the State of California to cause cancer.

TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

## Section 16 – Other Information

*CANADIAN DISTRIBUTOR: Sherwin-Williams Canada  
180 Brunel Rd.  
Mississauga, ON L4Z 1T5*

NOTE: These products have been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.