



Formulated for use with the
Color-Prime™ System

PREPRITE® 200

INTERIOR LATEX PRIMER B28W200

CHARACTERISTICS

- Best quality **wall** primer for general purpose use under **flats** and **enamels**
- Excellent coverage
- Excellent drywall sealer
- Covers dark colors, excellent for dramatic topcoat color changes

Use on interior:

- Drywall
- Masonry
- Concrete
- Previously Painted Surfaces

Color: White
Coverage: 400 sq ft/gal
@ 4 mils wet; 1.1 mils dry

Drying Time, @ 77°F, 50% RH:
temperature and humidity dependent

Touch: 1 hour
Recoat: 4 hours

Flash Point: N/A

Finish: 0-5 units @ 85°

Tinting - For best color development, use the recommended shade in the COLOR-Prime system. If desired, up to 4 oz per gallon of Blend-A-Color Toner can be used to approximate the topcoat color. Check color before use.

Vehicle Type: Vinyl Acrylic
B28W200

VOC (less exempt solvents):
86 g/L; 0.71 lb/gal

Volume Solids: 28 ± 2%

Weight Solids: 44 ± 2%

Weight per Gallon: 10.7 lb

Meets the performance requirements, not necessarily composition, of Federal Specification:

TT-P-650D, Type I
A-A-2994, Type II
A-A-2340

APPLICATION

Topcoat with latex, oil, water based epoxy, or solvent based epoxy on architectural applications.

Apply at temperatures above 50°F.
No reduction necessary.

Brush - Use a nylon/polyester brush.

Roller - Use a 3/8" - 3/4" nap synthetic cover.

Spray - Airless

Pressure 2000 psi

Tip017"-.021"

CLEANUP INFORMATION

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Drywall - Fill cracks and nail holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry Concrete, Cement - All surfaces must be cured. Remove all form release and curing agents. Masonry surfaces must be dry before priming. Moisture content must be 15% or lower, and the pH between 5 and 9.

108.01



PREPRITE® 200

INTERIOR LATEX PRIMER B28W200

SURFACE PREPARATION

Mildew

Remove before painting by washing with ProClean Professional™ Mildew Eliminator or a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

Caulking

Fill gaps between walls, ceilings, crown moldings, and other trim with Pro Select® Premium Siliconized Acrylic Latex Caulk 1100A after priming the surface.

CAUTIONS

For interior use only.
Protect from freezing.

LABEL CAUTIONS

CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, Call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.** LCE 10/18/01 B28W200 18 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.