



www.sherwin-williams.com

108.02

PREPRITE® 400 INTERIOR LATEX PRIMER B28W400

CHARACTERISTICS

- Good value **wall** primer for general use under **flats** and **enamels** wall paints
 - Ensures finish coat will cover when a moderate color change is required.
 - Good drywall sealer
- Use on interior:**
- Drywall
 - Masonry
 - Concrete
 - Previously Painted Surfaces

Color: White

Coverage: 350 - 400 sq ft/gal
@ 4 mils wet; 1.1 mils dry

Drying Time, @ 77°F, 50% RH:
temperature and humidity dependent

Touch: 1 hour
Recoat: 4 hours

Flash Point: N/A

Finish: 0-5 units @ 85°

Tinting - For better hiding of deeper colors, use up to 2 oz per gallon of Blend-A-Color Toner to approximate the topcoat color. Check color before use.

Vehicle Type: Vinyl Acrylic
B28W400

VOC (less exempt solvents):
61 g/L; 0.51 lb/gal

Volume Solids: 29 ± 2%

Weight Solids: 44 ± 2%

Weight per Gallon: 10.4lb

Provides performance which is comparable to the products that are formulated in accordance with federal specification:
TT-P-650D, Type I
A-A-2994, Type II

APPLICATION

Topcoat with architectural latex or oil finishes.

Apply at temperatures above 50°F.
No reduction necessary.

Brush - Use a nylon/polyester brush.

Roller - Use a 3/8" - 3/4" nap synthetic cover.

Pad

Spray - Airless

Pressure 2000 psi
Tip017"-.021"

CLEANUP INFORMATION

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with ProClean™ Prep Wash Concentrated Cleaner or other appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with PrepRite ProBlock Primer Sealer.

Drywall - Fill cracks and nail holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block - All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with PrepRite Masonry Primer.

108.02



PREPRITE® 400

INTERIOR LATEX PRIMER B28W400

SURFACE PREPARATION

Plaster - Must be cured, usually 30 days, and hard. If painting cannot wait, allow the surface to dry 7 days and prime with PrepRite Masonry Primer. Soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry before painting.

Mildew

Remove before painting by washing with ProClean™ Mildew Eliminator or a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

Caulking - Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with Pro Select™ Premium Siliconized Acrylic Latex Caulk 1100A after priming the surface.

CAUTIONS

For interior use only.
Protect from freezing.

LABEL CAUTIONS

CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, Call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

LCE 10/18/01 B28W400 15 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.