



Material Safety Data Sheet

Document Code: WeatherPerfect
Version: 01

Date of Preparation
September 27, 2001

Section 1 - Product and Company Identification

PRODUCT NAME & NUMBERS

WEATHER PERFECT® Exterior Latex Flat House & Trim Paint

Base C	B36G300	White	B36W306
Burgundy Base	B36R333	Extra White	B36W351
Perma White	(B36W300)	Base B	B36Y300
Tinting White	(B36W301)	Yellow Corn	B36Y304
Base A	B36W302		

HMIS CODES

Health	1*
Flammability	0
Reactivity	0

WEATHER PERFECT® Exterior Latex Satin House & Trim Paint

Base C	B77G500	Perma White	B77W506
Burgundy Base	B77R533	Extra White	B77W551
Tinting White	(B77W501)	Base B	B77Y500
Base A	B77W502		

MANUFACTURER'S NAME
THE SHERWIN-WILLIAMS COMPANY
101 Prospect Avenue N.W.
Cleveland, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917
INFORMATION TELEPHONE NO.
(216) 566-2902

Section 2 – Composition/Information on Ingredients

% WT.	CAS No.	Ingredient Name	Vapor Pressure
0-25	14808-60-7	Quartz	
		ACGIH TLV 0.05 mg/m3 as Respirable Dust	
		OSHA PEL 0.05 mg/m3 as Respirable Dust	
0.7-1	14464-46-1	Cristobalite	
		ACGIH TLV 0.05 mg/m3 as Respirable Dust	
		OSHA PEL 0.05 mg/m3 as Respirable Dust	
0-7	1332-58-7	Kaolin	
		ACGIH TLV 2 mg/m3 as Respirable Dust	
		OSHA PEL 10 mg/m3 Total Dust	
		OSHA PEL 5 mg/m3 Respirable Fraction	
0-19	13463-67-7	Titanium Dioxide.	
		ACGIH TLV 10 mg/m3 as Dust	
		OSHA PEL 10 mg/m3 Total Dust	
		OSHA PEL 5 mg/m3 Respirable Fraction	
0-1	1314-13-2	Zinc Oxide	
		ACGIH TLV 10 mg/m3 as Dust	
		OSHA PEL 10 mg/m3 Total Dust	
		OSHA PEL 5 mg/m3 Respirable Fraction	
0-0.5	1333-86-4	Carbon Black.	
		ACGIH TLV 3.5 mg/m3	
		OSHA PEL 3.5 mg/m3	
8	8007-18-9	Nickel Antimony Titanate	
(B36Y304 only)		ACGIH TLV 0.5 mg/m3	
		OSHA PEL 0.5 mg/m3	
<2% due to tinting	107-21-1	Ethylene Glycol.	
		ACGIH TLV 50 ppm CEILING	0.1 mm
		OSHA PEL 50 ppm CEILING	

Section 2 – Composition/Information on Ingredients (continued)

% WT.	CAS No.	Ingredient Name	Vapor Pressure
<2% due to tinting	14807-96-6	Talc	
		ACGIH TLV	2 mg/m3 as Respirable Dust
		OSHA PEL	2 mg/m3 as Respirable Dust

Section 3 – Hazards Identification

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For Complete Discussion of Toxicology Data Refer to Section 11.

Section 4 – First Aid Measures

- If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
- If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
- If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- If SWALLOWED: Do not induce vomiting. Get medical attention immediately.

Section 5 – Fire Fighting Measures

FLASH POINT	LEL	UEL
None	N.A.	N.A.

FLAMMABILITY CLASSIFICATION

Not Applicable

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 – Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

Section 7 – Handling and Storage

DOL STORAGE CATEGORY - Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

Section 8 – Exposure Controls/Personal Protection

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m³ (total dust), 3 mg./m³ (respirable fraction), OSHA PEL 15 mg./m³ (total dust), 5 mg./m³ (respirable fraction).

Removing or disturbing old paint from interior or exterior surfaces by sanding, scraping, abrading or other means may produce dust, debris or fumes that contain lead. Exposure to lead dust, debris or fumes may cause brain damage or other adverse health effects, especially in children and pregnant women. Structures built before 1978 should be tested by a licensed inspector prior to removing or disturbing old paint. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding, wirebrushing, abrading, burning or welding the dried film, wear a particulate respirator approved by NIOSH/MSHA for protection against non-volatile materials in Section 2.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section 9 – Physical and Chemical Properties

PRODUCT WEIGHT	9.1-11.1 lb/gal	EVAPORATION RATE	Slower than Ether
SPECIFIC GRAVITY	1.10-1.33	VAPOR DENSITY	Heavier than Air
BOILING POINT	212-477 °F	MELTING POINT	N.A.
VOLATILE VOLUME	66-69 %	SOLUBILITY IN WATER	N.A.
pH	9.5		
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)			
0.9-1.0 lb/gal	Less Federally Exempt Solvents		
0.3-0.4 lb/gal	Emitted VOC		

Section 10 – Stability and Reactivity

STABILITY - Stable

CONDITIONS TO AVOID - None known.

INCOMPATIBILITY - None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide, Oxides of Metals in Section 2

HAZARDOUS POLYMERIZATION - Will not occur

Section 11 – Toxicological Information

CHRONIC HEALTH HAZARDS

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

B36Y304 contains Nickel Antimony Titanate. Limited evidence exists linking certain Nickel compounds to cancer in animals and possibly humans, however no direct evidence exists that Nickel Antimony Titanate is carcinogenic.

Rats exposed to titanium dioxide dust at 250 mg./m³ developed lung cancer, however, such exposure levels are not attainable in the workplace.

TOXICOLOGY DATA

CAS No.	Ingredient Name			
14808-60-7	Quartz			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
14464-46-1	Cristobalite			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
1332-58-7	Kaolin			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
13463-67-7	Titanium Dioxide.			
	LC50	RAT	4HR	Not Established
	LD50	RAT		>7500 mg/kg
1314-13-2	Zinc Oxide			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
1333-86-4	Carbon Black.			
	LC50	RAT	4HR	Not Established
	LD50	RAT		>15400 mg/kg
8007-18-9	Nickel Antimony Titanate			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
107-21-1	Ethylene Glycol.			
	LC50	RAT	4HR	Not Established
	LD50	RAT		4700 mg/kg
14807-96-6	Talc			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established

Section 12 – Ecological Information

ECOTOXICOLOGICAL INFORMATION - No data available.

Section 13 – Disposal Considerations

WASTE DISPOSAL METHOD

Waste from B36Y304 may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for extractability to determine the applicable EPA hazardous waste numbers.

Waste from other products is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate all products in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 – Transport Information

DOT PROPER SHIPPING DESCRIPTION: Paint and Related Materials, NOIBN

IATA/IMDG SHIPPING DESCRIPTION: Paint and Related Materials, NOIBN

Section 15 – Regulatory Information

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
107-21-1	Ethylene Glycol.	<2	
	Zinc Compound.	0-1	0-1.2
	Nickel Compound. (<i>B36Y304 only</i>)	8	0.3
	Antimony Compound. (<i>B36Y304 only</i>)	8	1.0

CALIFORNIA PROPOSITION 65

WARNING: These products contain chemicals known to the State of California to cause cancer.

TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 – Other Information

CANADIAN DISTRIBUTOR: *Sherwin-Williams Canada
180 Brunel Rd.
Mississauga, ON L4Z 1T5*

NOTE: These products have been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.